



WCW68/98

Sounder with beacon for outdoor use EN 54-23

Description

Sounder with beacon for outdoor use and wall installation. 32 tones, 2 volumes and 2 selectable covers. Power supply from 10 to 60 Vdc and consumption from 8 to 14 mA, depending on the volume and coverage selected. Acoustic power from 98dB to 105 dB according to selected volume. Certified EN 54-23 and EN 54-23.

Flash coverage: W-3-7 (0,5Hz) or W-4-9 (1 Hz).

Available in red color (WCW98) and white color (WCW68)

Features

- Low current consumption
- 2 volume levels and 32 selectable tones
- 2 flash coverage
- Available in red and white colors
- Synchronized flash

Technical features

Sounder	
Operating voltage:	From 9 to 60 VDC
Alarm current consumption:	
- Coverage W-3-7	12.5 mA
- Coverage W-4-9	14.5 mA
Connections	
	2 x 1,5 mm ² twisted
Environment	
Operating temperature:	From -10°C to +55°C
Relative humidity:	95% without condensation
IP Index	IP65
Physical features	
Dimensions:	63 mm x 109 mm x 121 mm
Material:	ABS
Approvals	
	EN 54-23 and EN 54-3
Certificate number:	1328-CPR-0755